FABRINET Megadrain

Megadrain is a drainage product made of three-dimensional polypropylene monofilaments combined with two layers of polypropylene filter Non-Woven.

Megadrain has an extremely high voids content offering a high in-plane flow capacity. and are used for surface drainage applications, replacing conventional drainage gravel layers.



Characteristics	Test method	Unit	14-206		27-207		38-215		59-220		
Geocomposite											
Type of product		Drainage composite with filter Non-Woven filter on both sides									
Raw material	PP Monofilament core + PP Non-Woven										
Thickness (2 kPa)	EN ISO 9863-1	mm	5.5		7.0		15.5		20		
Tensile Strength (MD/CMD)	ISO 10319	kN/m	15 /15		15 /15		15 /15		15 /15		
In-plane Water Flow Capacity; MD a			(rigid/rigid)		(soft/rigid)		(soft/rigid)		(soft/rigid)		
			i=1	i=0.1	i=1	i=0.1	i=1	i=0.1	i=1	i=0.1	
20 kPa	ISO 12958	l/(m x s)	1.0	0.3	2.70	0.70	3.80	1.20	5.80	1.55	
50 kPa			0.9	0.27	2.30	0.57	2.00	0.85	2.50	0.70	
100 kPa			0.8	0.25	1.50	0.40	0.70	0.25	1.00	0.30	
Geotextile											
Mass per Unit Area	ISO 9864	g/m²	120		120		120		120		
Tensile Strength (MD/CMD)	ISO 10319	kN/m	7.5 / 7.5		7.5 / 7.5		7.5 / 7.5		7.5 / 7.5		
Cone drop test	ISO 13433	mm	36		36		36		36		
Puncture resistance	ISO 12236	Ν	1200		1200		1200		1200		
Characteristic Opening Size	ISO 12956	μm	90		90		90		90		
Water Flow Normal to Plane	ISO 11058	l/(m² x s)	90		90		90		90		
Supply specifications											
Roll Dimension - Width (±3%)		m	2.4		2.4		2.4		2.4		
Roll Dimension - Length (±2%)		m	25		63		33		25		
Area (Surface/Roll)		m²	62.5		151.2		79.2		62.5		
Roll diameter		mm	460		800		810		800		
Rolls per pallet				6		2		2		2	

NOTES:

All properties, unless otherwise noted, are guiding values. Minimum values are within 95% confidence interval. (a): Tolerance -30%

The information contained herein is provided for reference purposes only and is not intended as a warranty or guarantee. Final determination of suitability for use contemplated is the sole responsibility of the user. SOLMAX assumes no liability in connection with the use of this information.

Certification and Accreditation



Solmax is not a design or engineering professional and has not performed any such design services to determine if Solmax's goods comply with any project plans or specifications, or with the application or use of Solmax's goods to any particular system, project, purpose, installation, or specification.

